



规格说明: Specifications:

电气特性: Electrical:

- 额定电流: Current Rating  
3.1A/contact terminal
- 额定电压: Voltage Rating  
30V DC
- 接触电阻: Contact Resistance  
30 milliohms MAX
- 绝缘电压: Dielectric Withstanding Voltage:  
500 V AC AT Sea Level
- 绝缘电阻: Insulation Resistance:  
1000MEGA ohms MIN

物理性能: Mechanical:

- 插拔力: Connector Mate and Unmate Force  
Mate force: 3.57kgf(MAX)  
Unmate force: 1.02kgf(MIN)
- 端子保持力: Terminal Retention  
1.0kgf(MIN)

原材料: Material:

- 塑胶: Housing:  
Hing Temperature Ternmaplastics,

电镀: Finish:

- 端子: Contact: Plated Gold in Mating Area:  
Tin On Solder Tails
- 外壳: Shell:  
镀镍 40 微米 80U"(MIN) 镀  
端子 40 微米 50U"(MIN) 镀, 镀金区域 镀 100-200U" 镀金 1U"

TOLERANCE	APPROVALS	DATE	广东茂连科技有限公司 GUANGDONG MAOLIAN TECHNOLOGY CO. LTD						
X X.X X.XX X.XXX ANGULAR ±1° UNLESS OTHERWISE SPECIFIED	DRAWN NICKLE-SHEN CHECKED NICKLE-SHEN APPROVED	2019.05.28	MODEL TYPE: USB 2.0 CONNECTOR	DWG TYPE: CUST DWG	PROJECT CODE: PHD	DATE MM SCALE 1:1	SIZE A4	PART NO. ML-04XXN-4XV622-XX	REV. A0