



规格说明: Specifications:

电气性能: Electrical:

- 额定电流: Current Rating
3.1A/contact terminal
- 额定电压: Voltage Rating
30V DC
- 接触电阻: Contact Resistance
30 milliohms MAX
- 耐压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- 绝缘电阻: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

- 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
- 端子保持力: Terminal Retention
1.0kgf(MIN)

原材料: Material:

- 塑胶: Housing:
Hing Temperature Thermoplastics,

- 端子: Contact: Copper Alloy C2680

- 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

- 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails

端子四周镀50U"(MIN)镍,镀金区域镀100-200U"镀金1U"

- 外壳: Shell:
镍壳四周镀80U"(MIN)镍

Nickel Plating

TOLERANCE	APPROVALS	DATE	广东茂连科技有限公司 GUANGDONG MAOLIAN TECHNOLOGY CO. LTD			
X, X.X X.XX X.XXX ±0.15	DRAWN NICKLE-SHEN	2019.05.28	MODEL TYPE:	UNIT:	SIZE:	PART NO.
UNLESS OTHERWISE SPECIFIED	CHECKED NICKLE-SHEN	2019.05.28	USB 2.0 CONNECTOR	mm	A4	ML-04XXN-4XV623-XX
	APPROVED			SCALE	SHEET	DWG NO.
	CUST DWG	PHD		1:1	1 OF 1	
						REV.
						A0